

Glasvezelversterkte polyamide LED armaturen Ex de Glass fiber reinforced polyester LED lighting fixtures Ex de

Technische informatie:

Ex markering: II 2G Ex de eb mb op is q IIC T6/T5 Gb
 II 2D Ex tb IIIC T80°C / T85°C Db
 Geschikt voor zone 1, 2, 21 en zone 22
 Omgevingstemperatuur (T4): -25°C tot +40°C
 Omgevingstemperatuur (T5): -25°C tot +55°C
 Beschermingsgraad: IP66
 Spanning: 100~250 VAC - 50/60Hz
 Voorzien van 1 of 2 stuks LED unit 30 Watt
 Kleur 5700 K
 Kabelingangen: 3xM25
 Aansluitingen: 4 mm²
 Materiaal behuizing: glasvezelversterkt polyester
 Materiaal kap: polycarbonaat

Uitvoering met batterij tbv noodverlichting - alleen T4:
 Laadtijd: 24 uur
 Noodverlichting duur: >120 min.

Conform de standaards: EN60079

Technical data:

Ex mark: II 2G Ex db eb mb op is q IIC T6/T5 Gb
 II 2D Ex tD IIIC T80°C / T85°C Db
 Can be used in zone 1, 2, 21 and zone 22
 Ambient temperature range (T4) : -25°C to +40°C
 Ambient temperature range (T5) : -25°C to +55°C
 Degree of protection: IP66
 Voltage: 100~250 VAC - 50/60Hz.
 Complete with 1 or 2 pcs LED unit 30Watt
 Colour 5700 K
 Cable entries: 3xM25
 Connections: 4 mm²
 Material body: glass fibre reinforced polyester
 Material cover: polycarbonate

Version with battery for emergency lighting, only T4:
 Charging time: 24 hour
 Emergency light duration: > 120 min.

Meets the standards: EN60079

Afbeelding Illustration	Vermogen Power	Lumen	Gewicht Weight	Type
<p>Standaard armatuur Standard fixture</p>	1 x 30W	type 1 - 3700 type 2 - 3000	5.5 kg	Z0865 / 1xLED30W □
	2 x 30W	type 1 - 3700 type 2 - 3000	8.9 kg	Z0866 / 2xLED30W □
	1 x 30W Emergency -10W	type 1 - 3700 type 2 - 3000	8.6 kg	Z0865 / 1xLED30W □ -YJ
	2 x 30W Emergency -10W	type 1 - 3700 type 2 - 3000	12.1 kg	Z0866 / 1xLED30W □ -YJ
<p>Paalopzet armatuur Pole mounted fixture</p>	1 x 30W	type 1 - 3700 type 2 - 3000	5.5 kg	Z0865 / 1xLED30W □-P
	2 x 30W	type 1 - 3700 type 2 - 3000	8.9 kg	Z0866 / 2xLED30W □-P
	1 x 30W Emergency -10W	type 1 - 3700 type 2 - 3000	8.6 kg	Z0865 / 1xLED30W □ -P-YJ
	2 x 30W Emergency -10W	type 1 - 3700 type 2 - 3000	12.1 kg	Z0866 / 1xLED30W □ -P-YJ

type 1 = zonder diffusor / type 2 = met diffusor
 type 1 = without diffuser / type 2 = with diffuser

Lichtkarakteristiek Luminous intensity curve

