

LED noodverlichting armaturen Ex LED Emergency lighting fixtures Ex

Technische informatie:

Ex markering: Ⓜ II 2G Ex eb ib op is q IIC T4 Gb
 Ⓜ II 2D Ex tb IIIC T80°C Db
 Geschikt voor zone 1, 2, 21 en zone 22
 Omgevingstemperatuur : -25°C tot +55°C
 Beschermingsgraad: IP66
 Spanning: 100~250 VAC - 50/60Hz - 3Watt - 160 Lm
 Noodverlichting duur: >120 min
 Laadtijd: 24 uur
 Kabelingangen: 3xM25
 Aansluitingen: 2,5 mm
 Materiaal behuizing: Høogwaardig plastic - CMS
 Materiaal kap: polycarbonaat

Conform de standaards: EN60079



Technical data:

Ex mark: Ⓜ II 2G Ex eb 1b op is q IIC T4 Gb
 Ⓜ II 2D Ex tb IIIC T80°C Db
 Can be used in zone 1, 2, 21 and zone 22
 Ambient temperature range: -25°C to +55°C
 Degree of protection: IP66
 Voltage: 100~250 VAC - 50/60 Hz - 3 Watt - 160 Lm
 Emergency illuminating time > 120 min
 Recharging time: 24 hours
 Cable entries: 3xM25
 Connections: 2.5 mm²
 Material body: sheet moulding compound
 Material cover: polycarbonate

Meets the standards: EN60079

Afbeelding Illustration	Omschrijving Discription	Gewicht Weight	Type
	Noodverlichting - continu brandend Emergency light - light continu on	3.2 kg	Z0264 / 20-LED3W - M - KF - B
	Noodverlichting - aan bij spanningsuitval Emergency light - light on by disconnected power	3.2 kg	Z0264 / 20-LED3W - NM - KF - B
	Batterij 1,5Ah/6V Battery 1,5Ah/6V		Z0819/1.5-6
	Pictogram - vluchtweg links Pictogram - escape route on the left		Z0264 / Pictogram type 1
	Pictogram - vluchtweg rechts Pictogram - escape route on the right		Z0264 / Pictogram type 2
	Pictogram - vluchtweg naar onder Pictogram - escape route to below		Z0264 / Pictogram type 3
	Pictogram - vluchtweg omhoog of rechtdoor Pictogram - escape route up or straigh on		Z0264 / Pictogram type 4
	Pictogram - EXIT Pictogram - EXIT		Z0264 / Pictogram type 5

Afmetingen Dimensions

